

# FEATURES

Compaq ProLiant 5500

## Compaq ProLiant 5500 6/200

### System Unit

|                   |  |
|-------------------|--|
| Microprocessor    | 200-MHz Intel Pentium® Pro processor                       |
| Upgradability     | Upgradable to quad processing                              |
| Cache             | 512-KB level 2 writeback ECC protected cache per processor |
| Processor Sockets | 4  |
| Expansion Slots   |  |
| I/O (Total)       | 8, 7 available   |
| PCI               | 5  |
| Shared PCI/EISA   | 3  |
| RAM               |  |
| Standard          | 128 MB   |
| Maximum           | 3 GB   |

### Network Interface Controllers

|   |                          |
|---|--------------------------|
| Netelligent 100 FDDI PCI SAS<br>Fiber-SC      | Optional                 |
| Netelligent 100 FDDI PCI SAS<br>Fiber-MIC     | Optional                 |
| Netelligent 100 FDDI PCI DAS<br>Fiber-SC      | Optional                 |
| Netelligent 100 FDDI PCI SAS UTP              | Optional                 |
| Netelligent 100 FDDI PCI DAS UTP              | Optional                 |
| Netelligent 100 FDDI EISA SAS<br>Fiber-MIC    | Optional                 |
| Netelligent 100 FDDI EISA DAS<br>Fiber-MIC    | Optional                 |
| Netelligent 100 FDDI EISA SAS UTP             | Optional                 |
| Netelligent 100 FDDI EISA DAS UTP             | Optional                 |
| Netelligent 10/100 TX PCI UTP                 | Standard                 |
| Netelligent 10 T/2 PCI UTP/Coax<br>Controller | Optional                 |
| Netelligent 10 T PCI UTP                      | Optional                 |
| Netelligent 16/4 TR PCI IBM UTP/STP           | Optional                 |
| Netelligent 4/16 TR PCI UTP/STP               | Optional                 |
| Netelligent Dual 10/100 TX PCI UTP            | Optional                 |
| NetFlex-3/P                                   |                          |
| 100 Base-TX Upgrade Module                    | Optional (for NetFlex-3) |
| 100Base-FX Upgrade Module                     | Optional (for NetFlex-3) |
| 100VG-AnyLAN Upgrade Module                   | Optional (for NetFlex-3) |

## Compaq ProLiant 5500 6/200

**Server Management**

|                               |          |
|-------------------------------|----------|
| Compaq Insight Manager        | Standard |
| Integrated Remote Console     | Standard |
| Integrated Management Display | Standard |
| Automatic Server Recovery-2   | Standard |
| Server Health Logs            | Standard |
| Recovery Server Option        | Optional |
| Compaq Remote Insight Board   | Optional |

**Storage**

|  |  |
|--|--|
| Diskette Drives  | 1.44-MB  |
| CD-ROM Drives  |  |
| Standard   | 16X Max <sup>1</sup> CD-ROM Drive IDE  |
| Optional   | IDE or SCSI  |
| Hard Drives <sup>2</sup>   |  |
| Standard   | None   |
| Optional   | 2.1-GB, 4.3-GB, 9.1-GB Wide-Ultra SCSI-3 Drives  |
|  | 2.1-GB, 4.3-GB, 9.1-GB, 18.2 GB Pluggable Wide-Ultra SCSI-3 Drives   |
|  | 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Hard Drives  |
| External Storage   |  |
| ProLiant Storage System, ProLiant Storage System Models/F1 and /F2 | Optional   |
| ProLiant Storage System Models/U1 and /U2                          |  |
| SCSI Storage Expander  | Optional   |
| CD-Storage System  |  |
| Tower Model  | Optional   |
| Maximum Storage Capacity   |  |
| Internal   | 127.4 GB (6 x 1.6-inch hot-plug internal hard drives) using 18.2-GB hard drives; 2 x 9.1-GB hard drives installed in available removable media bays                              |
| External   | 1.5 TB (12 ProLiant Storage Systems Model F1, each with 7 x 18.2-GB hard drive)  |
| Total  | 1.7 TB   |
| Tape Drives  |  |
| Optional   | 2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, TurboDAT AutoLoaders, 15/30-GB DLT, 35/70-GB DLT, DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2 |

## Compaq ProLiant 5500 6/200

### Storage *(cont'd)*

#### Controllers

|          |  |
|----------|--|
| Standard | Integrated Dual Channel Wide-Ultra SCSI-3  |
| Optional | Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, SMART 2/E Array, Dual Channel Wide-Ultra SCSI-3 |

### Interfaces

|                           |   |
|---------------------------|---|
| Parallel                  | 1 |
| Serial                    | 2 |
| Pointing Device (mouse)   | 1 |
| Graphics                  | 1 |
| Keyboard                  | 1 |
| External Fast-Wide SCSI-2 | 1 |
| Network RJ-45             | 1 |

### Graphics

|  |          |
|--|----------|
| Integrated 1024 x 768 by 256 color noninterlaced 1 MB Video System | Standard |
|--|----------|

### Monitors

|                                 |          |
|---------------------------------|----------|
| V55 Color                       | Optional |
| V75 Color                       | Optional |
| V90 Color                       | Optional |
| P50 Color                       | Optional |
| P75 Color                       | Optional |
| P110 Color                      | Optional |
| P1610 Color                     | Optional |
| TFT450 Flat Panel Color Monitor | Optional |
| TFT500 Flat Panel Color Monitor | Optional |

### LCD Displays

|                               |          |
|-------------------------------|----------|
| Integrated Management Display | Standard |
|-------------------------------|----------|

### Keyboard

|                    |          |
|--------------------|----------|
| Keyboard and Mouse | Standard |
|--------------------|----------|

### Supported System Software from Compaq

|  |          |
|--|----------|
| Compaq Insight Manager                   | Standard |
| Compaq SmartStart                        | Standard |
| Microsoft Windows NT Server 3.51 and 4.x | Optional |
| Novell intraNetWare                      | Optional |

Compaq ProLiant 5500 6/200

**Supported System Software  
from Compaq *(cont'd)***

|  |          |
|--|----------|
| Novell intraNetWare For Small Business | Optional |
| Novell intraNetWare SFT-III            | Optional |
| Novell intraNetWare SMP                | Optional |
| Novell NetWare 3.20 and 4.10           | Optional |
| IBM OS/2 2.x                           | Optional |
| IBM OS/2 Warp Family of Products       | Optional |
| SCO OpenServer 5                       | Optional |
| SCO UnixWare 2.1                       | Optional |
| Solaris X86 2.5.x and 2.6              | Optional |

<sup>1</sup> Data transfer rate will vary from 150KB/s to 2400 KB/s.

<sup>2</sup> Hard drive specifications may vary slightly depending on vendor.